


SUNLINQ™ Portable Solar Panel - 12 Watt

SUNLINQ™ is the only solution for portable solar power for all types of outdoor needs. The SUNLINQ™ 12 Watt is ideal for hiking, camping, sporting events, on campus and at the beach.

Incorporating solid state, thin-film, PowerFLEX™ solar cells, the SUNLINQ™ 12 Watt provides an excellent choice for excursions that require lightweight, flexible, durable portable power.

Product Specifications (SL-12)

Electrical Characteristics*	
SL Product Number	SL-12
Typical Current (milliamps) at 11V (at 62°C)	800
Nominal Operating Voltage	12V CLA**
Typical Power (Watts) at STC*	11
Maximum Limit for Open Circuit Voltage	15.6V
Maximum Power (Watts)	12
Thermal Characteristics	
Power (%/C)	-0.5
Voltage (%/C)	-0.5
Cell Temperature Operating Range	-40° F to 176° F/ -40° C to 80° C
Dimensions and Weight	
Folded	
Length, in (mm)	9 (229)
Width, in (mm)	5 (127)
Thickness, in (mm)	.7 (17.78)
Deployed	
Length, in (mm)	29.125 (740)
Width, in (mm)	17.5 (445)
Thickness, in (mm)	.03 (.762)
Weight	
Weight, lb (kg)	.7 (.32)
Max Power to weight ratio watt/lb (watt/kg)	17.1 (37.5)



SL-12 Watt

*Data at Standard Test Conditions (STC)
STC: irradiance level 1000W / m², spectrum AM 1.5 and cell temperature 25° C
**Cigarette Lighter Adapters (CLAs) typically operate best between 11V and 14.5V

